US Army Corps of Engineers® Pittsburgh District


ALLEGHENY RIVER BASIN
CONEMAUGH RIVER LAKE
PERMANENT EMBANKMENT AND
CULVERT REPAIR PROJECT
BLAIRSVILLE, INDIANA COUNTY PA




SOLICITATION NO: W911WN-17-B-8007 CONTRACT NO: W911WN-17-X-XXXX

ISSUE DATE: JULY 2017

CERTIFIED FINAL DOCUMENTS







PROJECT LOCATION MAP



PENNSYLVANIA ONE CALL SYSTEM, INC.
CALL 3 BUSINESS DAYS BEFORE YOU DIG!
1-800-242-1776 or 8-1-1

POCS Serial NO.:

SIGNATURES AFFIXED BELOW INDICATE (AND APPROVAL OF ALL DRAWINGS LISTE	
SUBMITTED BY:	
/s/ JESSICA C. FARMER, P.E.	14 JULY 2017
SECTION CHIEF	DATE
APPROVAL RECOMMENDED BY:	
/s/ BETH L. SCHNELLER, P.E.	14 JULY 2017
BRANCH CHIEF	DATE
APPROVED BY:	
/s/ JEANINE M. HOEY, P.E.	14 JULY 2017
CHIEF, ENGINEERING AND CONSTRUCTION DIVISION	DATE

THIS PROJECT WAS DESIGNED BY THE PITTSBURGH DISTRICT OF THE U.S. ARMY CORPS OF ENGINEERS AND THE A/E FIRMS IDENTIFIED ON THIS SHEET. THE INITIALS OR SIGNATURES AND REGISTRATION DESIGNATIONS OF U.S. ARMY CORPS OF ENGINEERS INDIVIDUALS APPEAR ON THESE PROJECT DOCUMENTS WITHIN THE SCOPE OF THEIR EMPLOYMENT AS REQUIRED BY ER 1110-1-8152.



											DESCRIPTION
											MARK
ISSUE DATE:	14 JULY 2017	SOLICITATION NO.:	W911WN-17-B-8007	. ON TONGTINO	CONTRACTION:			FII F NAMF:	/s/ JESSICA C, FARMER, P.E. AO38ab 100 G-0010 dan	DATE:	G-2017 12:46
DESIGNED BY:	S. MISSENDA	DRAWN BY:	B. BAKER	יאם עבועבוט	CHECKED DI.	LEARMER	J. 1 AINIVIE I	SUBMITTED BY:	 /s/ JESSICA C. FARM	SIZE: PLOT DATE:	ANSI D 31-AUG-2017 12:46
S OF ENGINEERS	S OF ENGINEERS	STY AVENUE	1 DA 15000	71 FA, 13222							

ALLEGHENY RIVER BASIN
CONEMAUGH RIVER LAKE
PERMANENT EMBANKMENT AND CULVERT REPAIR P
BLAIRSVILLE, PA
COVER SHEET

G-0010

DRAWING TITLE GENERAL E DRAWING INDEX IVIEW PLAN SURVEY
E DRAWING INDEX I VIEW PLAN
VIEW PLAN
VIEW PLAN
PLAN
SURVFY
CIVIL
ID LINING PLAN AND SECTION
/ERT SECTIONS
SHEET 1 OF 3
SHEET 2 OF 3
SHEET 3 OF 3
TIONS
Γ 1 OF 2
Γ 2 OF 2
IZATION DETAILS
E TYPE FE-5 DETAILS
EROSION AND SEDIMENTATION CONTROL
ONTROL PLAN
INITION DI ANIDECT MANNACEMENT DO ACTICE DETAILO
ONTROL PLAN BEST MANAGEMENT PRACTICE DETAILS
NTROL PLAN BEST MANAGEMENT PRACTICE DETAILS
.I.

	REFERENCE DRAWINGS
FILE NAME	DRAWING TITLE
PLATE_01-B	EXISTING CONDITIONS, SLOPE AREA FAILURE PLAN VIEW
PLATE_02-A	EXISTING & PROPOSED EMBANKMENT CONDITIONS
PLATE_03-B	EROSION AND SEDIMENT CONTROL PLAN AND FOOTPRINT OF TEMPORARY STABILIZATION BERM PLAN VIEW
PLATE_04-A	EROSION & SEDIMENTATION CONTROL PLAN BEST MANAGEMENT PRACTICE INSTALLATION AND MAINTENANCE NOTES AND ABBREVIATIONS
FIG 1	POOL STAGE HYDROGRAPHS 1952-1963
FIG 2	POOL STAGE HYDROGRAPHS 1964-1975
FIG 3	POOL STAGE HYDROGRAPHS 1976-1987
FIG 4	POOL STAGE HYDROGRAPHS 1988-1999
FIG 5	POOL STAGE HYDROGRAPHS 2000-2011
FIG 6	POOL STAGE HYDROGRAPHS 2012-2016
FIG 7	MISCELLANEOUS DETAILS - TEMPORARY STABILIZATION BERM CONSTRUCTION

POLYVINYL CHLORIDE

HIGH DENSITY POLYETHYLENE
IDENTIFICATION
AMERICAN ASSOCIATION OF STATE
HIGHWAY AND TRANSPORTATION OFFICIALS

WITH
COMPOST FILTER SOCK
BEST MANAGEMENT PRACTICE
ROCK CONSTRUCTION ENTRANCE

CENTRIFUGALLY CAST CONCRETE PIPE UNLESS NOTED GEOTEXTILE

PUMPED WATER FILTER BAG DIAMETER

ABBREVIATIONS:

USACE NTS STA EL	U.S. ARMY CORPS OF ENGINEERS NOT TO SCALE STATION ELEVATION	PVC HDPE ID AASHTO
T/ DWGS(S) REQ'D MAX MIN TYP C/C CONC CY CWL EA EQ C CTR HSE ABD APPROX TG INV MH GEN RM	TOP OF DRAWING(S) REQUIRED MAXIMUM MINIMUM TYPICAL CENTER TO CENTER CONCRETE CUBIC YARD CONTRACTOR WORK LIMITS EACH EQUAL CENTERLINE CONTROL HOUSE ABANDONED APPROXIMATE TOP GRATE INVERT MANHOLE GENERATOR ROOM	W/ CFS BMP RCE PWFB D CCCP UN GT
CMP	CORRUGATED METAL PIPE	

LEGEND:

LLOLIND.		
990 ———	MAJOR CONTOUR (EXISTING)	——— S D ———
	ZONE A - 100 YEAR FLOOD PLAIN BOUNDARY	ST
	EDGE OF WATER SURFACE	<u>s</u>
xx	FENCE LINE	
——— E _x ———	EXISTING OVERHEAD ELECTRIC LINE	©
E _x	EXISTING UNDERGROUND ELECTRIC LINE	•
—— s s _x —— (FORCE)	EXISTING SANITARY SEWER FORCE MAIN	•
—— s s _x ——	EXISTING SANITARY SEWER GRAVITY LINE	
——— S D _x ———	EXISTING STORM SEWER LINE	TB-2
——— G _x ———	EXISTING NATURAL GAS LINE	→
W _x	EXISTING WATER LINE	(ن ع
(ABD)	PIPING ABANDONED IN-PLACE	~~~
——— P L ———	PROPERTY LINE	
	LEGAL RIGHT-OF-WAY LINE	
	CONTRACTOR WORK LIMITS	
	LIMITS OF DISTURBANCE	
990 ———	MAJOR CONTOUR (PROPOSED)	


S D	NEW STORM SEWER LINE
ST	NEW 5' DIAMETER STORM SEWER MANHOLE
S	SANITARY SEWER MANHOLE
	STORM INLET
©	GAS METER
Θ	SANITARY SEWER CLEAN-OUT
•	UTILITY POLE
\longrightarrow	UTILITY POLE GUY WIRE
\bowtie	VALVE
⊕ ^{TB-2}	BORING LOCATIONS/NUMBER
()	TREE

IKEE

EXISTING VEGETATION LINE




EMBANKMENT CREST FILL AREA AREA OF RIPRAP EMBANKMENT PROTECTION





SULPHUR RUN BANK STABILIZATION AREA AND NEW STORM SEWER RIPRAP APRON

US Army Corps of Engineers®

SHEET ID ||G-0011-B|







		S	SURVEY CO	ONTROL	
	STATION NAME	GRID NORTHING	GRID EASTING	ELEVATION	DESCRIPTION
•	QUARRY	405140.25	1546154.45	992.85	ALUMINUM DISK STAMPED "QUARRY" ON 5/8" X 30"
•	CREEK	404656.11	1546073.89	940.09	ALUMINUM DISK STAMPED "CREEK"
	1001	405130.83	1546345.15	983.67	NAIL
	1002	405017.73	1546287.11	976.50	SCRIBE IN CONCRETE
	STA 0+81.80	404897.78	1546126.61	945.43	5/8" REBAR
Ī	STA 1+69.12	404939.43	1546203.33		DESTROYED
	MH-NSP-100			989.81	SANITARY SEWER MANHOLE
	948A-F	405059.46	1546139.56		USACE BOUNDRY DISK ON PIPE
	F-980-C	404702.51	1546249.78		USACE BOUNDRY DISK ON PIPE



N DATE

DESIGNED BY:	ISSUE DATE:
	02 JUNE 2017
	SOLICITATION NO.:
	W911WN-17-B-8007
CHECKED BY:	CONTRACT NO.:
J. JALBRZIKOWSKI	
SUBMITTED BY:	FILE NAME:
IELLER, P.E.	/s/ BETH L. SCHNELLER, P.E. AO38ab_204_V-1001.dgn
PLOT DATE:	
31-AUG-2017 12:46	12:46
	7

LEGEND:


NOTES:

- THE HORIZONTAL DATUM IS NAD83(2011). THE GRID COORDINATE SYSTEM IS PENNSYLVANIA SPCS SOUTH ZONE (FIPS 3702). THE UNITS ARE US SURVEY FEET. THE NAD83(2011) COORDINATES WERE DERIVED FROM A FIVE HOUR GNSS OCCUPATION OF 1001, CALCULATED BY NGS OPUS, AND CHECKED AGAINST NGS PID KX1056.
- 2. THE VERTICAL DATUM IS NAVD88. THE ELEVATION UNITS ARE FEET. ALL GNSS ELEVATIONS ARE BASED ON GEOID12B.
- 3. THE EXISTING MAPPING PROVIDED BY THE BOROUGH OF BLAIRSVILLE WAS ON AN ASSUMED HORIZONTAL COORDINATE SYSTEM AND AN ASSUMED VERTICAL DATUM. CONTROL POINTS STA 0+81.80 AND 1+69.12, BOTH 5/8" REBAR, WERE RECOVERED AND OBSERVED BY USACE SURVEYORS AND USED TO MOVE MAPPING TO THE SPCS. STA 1+69.12 HAS SINCE BEEN DESTROYED.
- 4. THE EXISTING DROP MANHOLE NSP-100 WAS USED AS THE REFERENCE POINT TO LOWER THE EXISTING BOROUGH OF BLAIRSVILLE MAPPING TO NAVD88.
- 5. THE AVERAGE COMBINED SCALE FACTOR (PA SOUTH ZONE) FOR THE PROJECT IS 0.99991766.
- 6. FILED DATA WAS COLLECTED IN JANUARY, MARCH, AND MAY OF 2017 BY USACE PITTSBURGH GEOSPATIAL SECTION.

0 40' 8 SCALE: 1"=40' SHEET ID V-1001


THE PROPOSED CONSTRUCTION SEQUENCE PRESENTS ONE POSSIBLE METHOD OF PERFORMING THE WORK. THE CONTRACTOR HAS THE ABILITY TO MODIFY THE SEQUENCE TO SUIT THEIR MEANS AND METHODS WHILE ADHERING TO ALL DEFINED CONSTRUCTION RESTRICTIONS. IF THE CONTRACTOR ELECTS TO MODIFY THIS SEQUENCE, ANY MODIFICATIONS SHALL BE APPROVED BY THE CONTRACTING OFFICER.


- 1. VERIFY AND CLEARLY MARK ALL EXISTING UTILITIES WITHIN THE CONTRACTOR'S WORK LIMITS.
- COORDINATE WITH CONTRACTING OFFICER AND BOROUGH OF BLAIRSVILLE TO PROVIDE ACCESS TO PUMP STATION
 FACILITIES TO BOROUGH PERSONNEL. COORDINATE WITH CONTRACTING OFFICER AND BOROUGH OF BLAIRSVILLE TO
 REMOVE EXISTING FENCING AND INSTALL ANY TEMPORARY FENCES AND GATES AS REQUIRED TO RESTRICT ACCESS TO
 THE SITE.
- 3. PROVIDE CONFINED SPACE ENTRY PERMIT PRIOR TO ANY WORK WITH THE EXISTING CULVERT STRUCTURE. INITIATE MONITORING TO ENSURE WORKER SAFETY WITHIN EXISTING CULVERT IN ACCORDANCE WITH APPROVED CONFINED SPACE ENTRY PLAN.
- 4. PERFORM A VIDEO SURVEY OF THE EXISTING CULVERT.
- 5. INSTALL TEMPORARY STREAM CROSSING, COMPOST FILTER SOCKS, PERFORM CLEARING AND GRUBBING AND TREE REMOVAL; INSTALL SANDBAG DIVERSION ALONG NORTH SPRING STREET, TEMPORARY INLETS, TEMPORARY SLOPE PIPES, INLET FILTER BAGS AND R-5 RIPRAP AT TEMPORARY SLOPE PIPE DISCHARGES.
- 6. INSTALL STONE ARCH CULVERT SUPPORT SYSTEM FROM STATION 3+53 TO 3+63.
- 7. INSTALL PIPE FLUME, TEMPORARY UPSTREAM SANDBAG DAM, AND DOWNSTREAM ROCK FILTER OR OTHER APPROVED DIVERSION TECHNIQUES.
- 8. EXCAVATE TEMPORARY STABILIZATION FEATURES AND MATERIAL FROM THE FAILED STONE ARCH CULVERT TO THE LINES AND GRADES SHOWN IN THE CONTRACT DOCUMENTS. PREPARE EXPOSED SOIL SLOPES TO EFFECT A SMOOTH, UNIFORM SURFACE FOR PLACEMENT OF GEOTEXTILE AND BEDDING MATERIAL. PERFORM THIS EXCAVATION IN A SEQUENCE SUCH THAT NO MORE MATERIAL THAN NECESSARY IS REMOVED AT ANY TIME PRIOR TO BACKFILLING WITH THE PERMANENT EMBANKMENT MATERIAL INSTALL SHORING, SHEETING, AND BRACING AS NEEDED. REMOVE AND DISPOSE OF STEEL PLATE AND CONCRETE BLOCKS FROM TEMPORARY STABILIZATION BUTTRESS. STORE R-4 FROM TEMPORARY STABILIZATION BERM AT CONTRACTOR LAYDOWN AREA FOR RE-USE.
 - 9. INSTALL MICROPILES AND FOOTER FOR CULVERT REPLACEMENT AND EXTENSION SECTIONS AND CONCRETE HEADWALL AND WINGWALL FOUNDATIONS.
 - 10. INSTALL STRUCTURAL PLATE OVER FOOTERS FOR CULVERT REPLACEMENT AND EXTENSION SECTIONS
 - 11. GROUT CULVERT KEY.
- extstyle 12. INSTALL STRUCTURAL BACKFILL AND GEOTEXTILE SEPARATION LAYER AT CULVERT REPLACEMENT.
- 13. FORM AND POUR CONCRETE HEADWALL END TREATMENT FOR ARCH CULVERT EXTENSION
- \triangle 14. INSTALL STRUCTURAL BACKFILL AND GEOTEXTILE SEPARATION LAYER AT CULVERT EXTENSION AND BEHIND HEADWALL/WINGWALLS.
- 15. INSTALL UPSTREAM CUT-OFF-KEY (SEE PLAN ON SHEET C-4012).
- 16. (BASE AWARD) INSTALL CCCP LINER IN STONE ARCH CULVERT AND CULVERT REPLACEMENT SECTION BETWEEN STATION 2+95
 AND STATION 3+80 (SEE PLAN ON SHEET C-4012). FLOWLINE SHALL BE LINED WITH INVERT REPAIR MORTAR BETWEEN STATION
 2+78 AND STATION 4+20. ALTER POSITIONING OF PIPE FLUME OR OTHER APPROVED DIVERSION TECHNIQUES AS REQUIRED FOR
 LATERAL PHASING OF THIS WORK.
- 17. (IF AWARDED) INSTALL UPSTREAM OPTION CCCP LINER IN STONE ARCH CULVERT BETWEEN STATIONS 3+80 AND 4+20. ALTER POSITIONING OF PIPE FLUME AS REQUIRED FOR LATERAL PHASING OF THIS WORK.
- 18. (IF AWARDED) INSTALL DOWNSTREAM OPTION CCCP LINER IN EXISTING STRUCTURAL PLATE AND CULVERT EXTENSION BETWEEN STATIONS 2+71 AND 2+95 (SEE PLAN ON SHEET C-4012). ALTER POSITIONING OF PIPE FLUME AS REQUIRED FOR LATERAL PHASING
- 19. INSTALL GEOTEXTILE FABRIC AND ROCK FILL EMBANKMENT TO THE LINES AND GRADES SHOWN ON CONTRACT DRAWINGS, INCLUDING SAND BEDDING LAYER, ANCHOR TRENCHES, AND EMBANKMENT CREST AND TRANSITION ZONES. RE-USE STORED R-4 FROM TEMPORARY STABILIZATION BUTTRESS AS APPROVED BY THE CONTRACTING OFFICER. COMPLETE CONSTRUCTION USING NEW R-4 MATERIAL FROM APPROVED SOURCES.
- 20. INSTALL REQUIRED BANK ARMORING (BASE AWARD).
- 1. REMOVE DOWNSTREAM ROCK FILTER, PIPE FLUME AND TEMPORARY UPSTREAM SANDBAG DAM.
- 22. (IF AWARDED) INSTALL APPROVED FLOW DIVERSION STRUCTURES FOR EXTENDED BANK ARMORING.
- 23. (IF AWARDED) INSTALL EXTENDED BANK ARMORING.
- 24. (IF AWARDED) REMOVE FLOW DIVERSION STRUCTURES FOR EXTENDED BANK ARMORING.
- 25. INSTALL NEW CHAIN LINK SECURITY FENCE.
- 26. REMOVE TEMPORARY INLETS AND TEMPORARY SLOPE PIPES.
- 27. SEED, FERTILIZE, LIME, AND MULCH AREAS THAT HAVE BEEN DISTURBED BY THE CONSTRUCTION ACTIVITY.
 - 28. INSTALL TEMPORARY EROSION CONTROL BLANKETS ON ALL SLOPES GREATER THAN 3:1 AND ALONG THE STREAM BANKS.
 - 29. TEMPORARY STREAM CROSSING SHALL BE REMOVED AND RESTORED TO PRE-CONSTRUCTION CONDITIONS AS SHOWN. STONE USED TO CONSTRUCT CROSSING SHALL BE SPREAD ALONG TEMPORARY ACCESS ROAD.
 - 30. TREES, BRUSH, EXCESS SOIL AND CONSTRUCTION WASTE FROM THE CONSTRUCTION AND DEMOLITION ACTIVITIES SHALL BE DISPOSED OF OFF-SITE AT AN APPROVED FACILITY.
 - 31. ONCE THE SITE HAS BEEN STABILIZED AND REACHED A UNIFORM 70% PERENNIAL VEGETATIVE COVER, THE COMPOST FILTER SOCKS SHALL BE CUT OPEN AND THE WOODEN STAKES AND MESH SHALL BE REMOVED FROM THE SITE AND DISPOSED OF PROPERLY FOLLOWING THE BMP INSTALLATION NOTES.





H4TSDRST 0.083334:1

CERTIFIED FINAL DOCUMENTS










SHEET ID


||C-5014-B|

US Army Corps

of Engineers®


0.083334:1






- 1000 EDGE OF EXISTING
ASPHALT DRIVEWAY - 990 990 – EXISTING GROUND 980 - 980 -EMBANKMENT ROCK FILL (R-4) **–** 970 970 STRUCTURE **BACKFILL** EXISTING -GROUND ~ NEW HEADWALL ANCHOR TRENCH (SIMILAR TO DETAIL 1, THIS SHEET) (WINGWALL) 960 - 960 -STREAMBANK STABILIZATION (R-5) GEOTEXTILE SEPARATION LAYER (GT) WITH BEDDING (SEE DETAIL 2, THIS SHEET) - 950 950 / STRUCTURE BACKFILL 0+60 0+90


SECTION - EMBANKMENT REPAIR C-1011 SCALE: 1" = 10'



SECTION - EMBANKMENT REPAIR C-1011 SCALE: 1" = 10'



DETAIL - ANCHOR TRENCH (TYP) C-3017 C-4012



DETAIL - GEOTEXTILE WITH BEDDING


NOTES: 1. SAND BEDDING SHALL MEET THE REQUIREMENTS OF SPEC SECTION 31 00 00 SECTION 3.12.5. US Army Corps of Engineers®

SHEET ID

C-3017-B

CERTIFIED FINAL DOCUMENTS

10.00002:1




¢ CULVERT FOOTER REINFORCING SYMMETRICAL ABOUT CENTERLINE OF CULVERT


SECTION - FOOTER REINFORCING - TOP LAYER

HOOK BARS THAT CANNOT MEET THE DIMENSION REQUIREMENTS FOR EXTENDING BEYOND THE OUTERMOST BAR. HOOK DIMENSIONS SHOULD BE AS FOLLOWS: EXPOSED FACE: 2'-5" BACK FACE: 4'-2" ¬ - ADDED VERTICAL REBAR SIZE TO MATCH TYPICAL VERTICAL REBAR FOR WALL (TYP) B C-5019 – ADDED HORIZONTAL REBAR SIZE TO MATCH TYPICAL HORIZONTAL REBAR FOR WALL (TYP) INTERRUPTED BARS NOT SHOWN FOR CLARITY (TYP)

DETAIL - WINGWALL REINFORCING AT PIPE PENETRATION SCALE: 3/8" = 1'-0"



SECTION - FOOTER REINFORCING - BOTTOM LAYER C-5018



B C-5019 SECTION - WINGWALL REINFORCING AT PIPE PENETRATION SCALE: 3/8" = 1'-0"

> NOTE: 1. WORK THIS DRAWING WITH SHEET C-5018.

2. ALL BENDS AND HOOKS OF REINFORCEMENT SHALL BE PER ACI DETAILING MANUAL.

SCALE: 3/8"=1'

0.083334:1 H4TSDRST

CERTIFIED FINAL DOCUMENTS

US Army Corps of Engineers®

SHEET ID

C-5019-A


LIMITS OF EXCAVATION 7 □ LIMITS OF EXCAVATION 12' (MIN) 1.75 **EXISTING** LOW FLOW GROUND -WATER SURFACE -SLOPE VARIES GEOTEXTILE EMBEDMENT (SEE NOTE) -**GEOTEXTILI** (TYP.) R-5 STONE PROTECTION -

DIMENSIONS OF BANK STABILIZATION SHOWN ARE APPROXIMATE. DIMENSIONS OF BANK STABILIZATION VARY, BUT SHALL EXTEND TO THE TOP OF THE BANK OR NO LESS THAN 4 FEET. SLOPES VARY TO CONFORM TO EXISTING GROUND, BUT SHALL BE NO STEEPER THAN 1.75H:1V. FINAL DIMENSIONS SHALL BE DETERMINED IN THE FIELD.

9'-0"



TYPICAL SECTION - REQUIRED MINIMUM BANK ARMORING





NOTE:


DIMENSIONS OF BANK STABILIZATION SHOWN ARE APPROXIMATE. DIMENSIONS OF BANK STABILIZATION VARY, BUT SHALL EXTEND TO THE TOP OF THE BANK OR NO LESS THAN 4 FEET. SLOPES VARY TO CONFORM TO EXISTING GROUND, BUT SHALL BE NO STEEPER THAN 1.75H:1V. FINAL DIMENSIONS SHALL BE DETERMINED IN THE FIELD.



TYPICAL SECTION - EXTENDED BANK ARMORING








TYPE M TOP

NOTE:

- 1. PRECAST CONCRETE TO HAVE A COMPRESSIVE STRENGTH OF 4000 PSI WITHIN 28 DAYS.
- 2. ALL REINFORCEMENT TO HAVE A MINIMUM 1 1/2" CONCRETE COVER.
- 3. ALL OUTSIDE CORNERS TO HAVE A 1/2" X 1/2" CHAMFER
- 4. ALL TOLERANCES SHALL BE +/- 1/4" UNLESS NOTED.
- 5. SEE RC-45M SHEET 2 FOR REINFORCING DETAILS 6. SEE RC-45M SHEET 8 FOR STRUCTURAL STEEL BICYCLE SAFE GRATE.



TOP VIEW

KNOCK OUT SIZES


WALL A AND C = 26" X 36" WALL B AND D = 24" SQ.

NOTE:

- 1. PRECAST CONCRETE TO HAVE A COMPRESSIVE STRENGTH OF 4000 PSI WITHIN
- 2. THE INLETS AND GRATES SHALL MEET THE REQUIREMENTS OF SPECIFICATIONS SECTION 01 57 23.00 08 STORM WATER POLLUTION CONTROL.


TYPICAL SECTION - TYPE M INLET X-1001





40.48	ANCI 01 10 2017 12:48	O IONO	
	PLOT DATE:	SIZE:	
AO38ab_886_C-5020-A.d	/s/ ERICH D. GUY, P.E.	/s/ ERICH	
FILE NAME:	ED BY:	SUBMITTED BY:	
		E. GUY	
CONTRACT NO.:	BY:	CHECKED BY:	
W911WN-17-B-8007	B. BAKER/B. CRATTY	B. BAKER	
SOLICITATION NO.:	γ:	DRAWN BY:	
A. MARKUM/C. MARTIN 14 JULY 2017	M/C. MARTIN	A. MARKU	
ISSUE DATE:) BY:	DESIGNED BY:	

SHEET ID ||C-5020-A|



	STEEL PO	OST SCHEDULE	
USE AND SECTION	MINIMUM OL	JTSIDE DIMENSIC	ONS (NORMAL)
	FABRIC WIDTH 72" OR LESS	FABRIC WIDTH 84" TO 96"	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS TUBULAR - ROUND	2.375" O.D.	2.875" O.D.	4.00" O.D.
LINE POSTS TUBULAR - ROUND	1.90" O.D.	2.375" O.D.	2.875" O.D.
TOP, BOTTOM, & BRACE RAILS TUBULAR - ROUND		1.66" O.D.	

NOTES:

- DETAILS SHOWN ARE TO CLARIFY REQUIREMENTS AND ARE NOT INTENDED TO LIMIT OTHER TYPES OF FENCE SECTIONS AND METHODS OF INSTALLATION THAT COMPLY WITH THE SPECIFICATIONS.
- 2. WIRE TIES, RAILS, POSTS, AND BRACES SHALL BE CONSTRUCTED ON THE SECURE SIDE OF THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE THE SECURE AREA.
- 3. C-SECTION POSTS SHALL BE INSTALLED SO THAT THE VOID INSIDE THE POST IS COMPLETELY FILLED WITH CONCRETE UP TO THE TOP OF THE FOUNDATION.
- 4. CONCRETE SHALL BE 4,000 PSI COMPRESSIVE STRENGTH CONCRETE.
- BOROUGH OF BLAIRSVILLE TO PROVIDE EXISTING ENTRANCE GATE SECTION. CONTRACTOR SHALL RE-INSTALL GATE SECTION TO WORKING CONDITIONS.

FENCE LEGEND:

FE-5: CHAIN-LINK FENCE WITHOUT BARBED-WIRE APRON
TBR: FENCE WITH TOP RAIL AND TENSION WIRE AT BOTTOM
96: FABRIC WIDTH

10'-0" (MAX)

POST


WIRE

- TENSION

NOTE: PROVIDE BRACE PANEL WHENEVER STRAIGHT RUNS EXCEED 500 FEET

-BRACE RAIL

BRACE PANEL DETAIL



PULL POST -

-BRACE RAIL-

TRUSS ROD-


10'-0" (MAX)

LINE


POST

WIRE ¬

TENSION




TENSION BAND DETAIL



BRACE RAIL CLAMP DETAIL


FASTENING DETAILS



9 GAGE STEEL TIE WIRES (2'-0" O.C. MAX)


TOP OR BRACE RAIL ATTACHMENT





ROUND POST

LINE POST ATTACHMENT





	DESIGNED BY:	D BY:	ISSUE DATE:
	C. MARTIN	7	
	DRAWN BY:		SOLICITATION NO.:
	B. CRATTY	>	W911WN-17-B-8007
7770	CHECKED BY:	BY:	CONTRACT NO.:
	J. RUSNAK	×	
	SUBMITTED BY:	ED BY:	FILE NAME:
			AO38ab_886_C-5021.dgr
	SIZE:	PLOT DATE:	
	ANSI D	31-AUG-2017 12:48	12:48

CONEMAUGH RIVER BASIIN
CONEMAUGH RIVER LAKE
ERMANENT EMBANKMENT AND CULVERT REPAIR PROJECT
BLAIRSVILLE, PA
CHAIN LINK SECURITY FENCE TYPE FE-5

C-5021

0.083333:1





1 DETAIL - TEMPORARY STREAM CROSSING
NTS

US Army Corps of Engineers®


ALLEGHENY RIVER BASIN
CONEMAUGH RIVER LAKE
PERMANENT EMBANKMENT AND CULVERT REPAIR PROJI
BLAIRSVILLE, PA
EROSION AND SEDIMENT CONTROL PLAN

X-5002

0.083333:1

PLAN VIEW

HEAVY-DUTY LIFTING STRAPS (RECOMMENDED)



ELEVATION


NOTES:


1. LOW VOLUME FILTER BAGS SHALL BE MADE FROM NON-WOVEN GEOTEXTILE MATERIAL SEWN WITH HIGH STRENGTH, DOUBLE STITCHED "J" TYPE SEAMS. THEY SHALL BE CAPABLE OF TRAPPING PARTICLES LARGER THAN 150 MICRONS. HIGH VOLUME FILTER BAGS SHALL BE MADE FROM WOVEN GEOTEXTILES THAT MEET THE FOLLOWING STANDARDS:

PROPERTY	TEST METHOD	MINIMUM STANDARD
AVG WIDE WIDTH STRENGTH	ASTM D-4884	60 LB/IN
GRAB TENSILE	ASTM D-4632	205 LB
PUNCTURE	ASTM D-4833	110 LB
MULLEN BURST	ASTM D-3786	350 PSI
UV RESISTANCE	ASTM D-4355	70%
AOS % RETAINED	ASTM D-4751	80 SIEVE

- 2. A SUITABLE MEANS OF ACCESSING THE BAG WITH MACHINERY REQUIRED FOR DISPOSAL PURPOSES SHALL BE PROVIDED. FILTER BAGS SHALL BE REPLACED WHEN THEY BECOME ONE-HALF FULL OF SEDIMENT. SPARE BAGS SHALL BE KEPT AVAILABLE FOR REPLACEMENT OF THOSE THAT HAVE FAILED OR ARE FILLED. BAGS SHALL BE PLACED ON STRAPS TO FACILITATE REMOVAL UNLESS BAGS COME WITH LIFTING STRAPS ALREADY ATTACHED.
- 3. BAGS SHALL BE LOCATED IN WELL-VEGETATED (GRASSY) AREAS, AND DISCHARGE ONTO AREAS THAT ARE STABLE AND EROSION-RESISTANT. WHERE THIS IS NOT POSSIBLE, A GEOTEXTILE UNDER-LAYMENT AND FLOW PATH SHALL BE PROVIDED. BAGS MAY BE PLACED ON FILTER STONE TO INCREASE DISCHARGE CAPACITY. BAGS SHALL NOT BE PLACED ON SLOPES GREATER THAN 5%. FOR SLOPES EXCEEDING 5%, CLEAN ROCK OR OTHER NON-ERODIBLE AND NON-POLLUTING MATERIAL MAY BE PLACED UNDER THE BAG TO REDUCE SLOPE STEEPNESS.
- 4. NO DOWNSLOPE SEDIMENT BARRIER IS REQUIRED FOR MOST INSTALLATIONS. COMPOST BERM OR COMPOST FILTER SOCK SHALL BE INSTALLED BELOW BAGS LOCATED IN HQ OR EV WATER-SHEDS, WITHIN 50 FEET OF ANY RECEIVING SURFACE WATER OR WHERE GRASSY AREA IS NOT AVAILABLE.
- 5. THE PUMP DISCHARGE HOSE SHALL BE INSERTED INTO THE BAGS IN THE MANNER SPECIFIED BY THE MANUFACTURER AND SECURELY CLAMPED. A PIECE OF PVC PIPE IS RECOMMENDED FOR
- 6. THE PUMPING RATE SHALL BE NO GREATER THAN 750 GPM OR ONE-HALF THE MAXIMUM SPECIFIED BY THE MANUFACTURER, WHICHEVER IS LESS. PUMP INTAKES SHOULD BE FLOATING AND SCREENED.
- 7. FILTER BAGS SHALL BE INSPECTED DAILY. IF ANY PROBLEM IS DETECTED, PUMPING SHALL CEASE IMMEDIATELY AND NOT RESUME UNTIL THE PROBLEM IS CORRECTED.

DETAIL - PUMPED SEDIMENT REMOVAL SYSTEM X-1001






NOTES:

- 1. REMOVE DEPOSITS WHEN SEDIMENT ACCUMULATION IS ONE-HALF THE HEIGHT OF THE EXPOSED COMPOST FILTER SOCK.
- 2. PLACE COMPOST FILTER SOCK ON LEVEL GRADE. EXTEND BOTH ENDS OF THE COMPOST FILTER SOCK AT LEAST 8'-0" UPSLOPE AT 45 DEGREES TO THE MAIN ALIGNMENT.
- 3. REPLACE BIODEGRADEABLE FILTER SOCK AFTER 6 MONTHS; PHOTODEGRADEABLE AFTER 12 MONTHS.
- 4. OVERLAP COMPOST FILTER SOCK SECTIONS 8' (MIN).

DETAIL - COMPOST FILTER SOCK X-1001




- DRAWINGS PRIOR TO INSTALLING THE BLANKET.
- 2. PROVIDE ANCHOR TRENCH AT THE TOE OF THE SLOPE IN SIMILAR FASHION AS AT THE TOP OF THE SLOPE.
- 3. SLOPE SURFACE SHALL BE FREE OF ROCKS, CLODS, STICKS AND GRASS.
- 4. BLANKET SHALL HAVE GOOD CONTINUOUS CONTACT WITH UNDERLYING SOIL THROUGHOUT THE ENTIRE LENGTH. LAY BLANKET LOOSELY AND STAKE OR STAPLE TO MAINTAIN DIRECT CONTACT WITH SOIL. DO NOT STRETCH BLANKET.
- 5. THE BLANKET SHALL BE STAPLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- 6. BLANKETED AREAS SHALL BE INSPECTED WEEKLY AND AFTER EACH RUNOFF EVENT UNTIL PERRENIAL VEGETATION IS ESTABLISHED TO A MINIMUM 70% COVERAGE THROUGHOUT THE BLANKETED AREA. DAMAGED OR DISPLACED BLANKETS SHALL BE RESTORED OR REPLACED WITHIN 4 CALENDAR DAYS.



DETAIL - EROSION CONTROL BLANKET INSTALLATION


US Army Corps of Engineers®



	DESIGNED BY:	ISSUE DATE:
U.S. AKMI CORPS OF ENGINEERS	C. MARTIN	14 JULY 2017
	DRAWN BY:	SOLICITATION NO.:
1000 LIBERTT AVENUE	B. CRATTY	W911WN-17-B-8007
FII I SBURGH FA, 13222	CHECKED BY:	CONTRACT NO.:
	J RUSNAK	
	SUBMITTED BY:	FILE NAME:
	/s/ JAMES T. SHIBATA, P.E. AO38ab_886_X-5003.dc	AO38ab_886_X-5003.dg
	SIZE: PLOT DATE:	
	ANSI D 31-AUG-2017 12:48	12:48

SHEET ID X-5003

0.083333:1




SHEET ID

X-5004

US Army Corps of Engineers®

10:1



US Army Corps of Engineers®

0.083333:1

H4TSDRST

CERTIFIED FINAL DOCUMENTS

SHEET ID

X-5005

ROCK CONSTRUCTION ENTRANCE

BMP INSTALLATION NOTES

- A. STOCKPILE RCE STONE NEAR FOR DAILY REPAIR REQUIREMENTS. MAINTAIN 8" (INCH) THICKNESS OF AASHTO #1 THROUGHOUT CONSTRUCTION.
- B. INSPECT RCE DAILY. REMOVE ACCUMULATED SEDIMENTS DAILY.
- C. REPLACE ALL ROCK WHEN SURFACE BECOMES CLOGGED WITH SOIL AND THE ABILITY TO TRAP MATERIAL HAS BEEN LOST.

PUMPED WATER FILTER BAG

- A. SET UP PUMPED WATER FILTER BAG CLOSE TO THE WORK AREA. EASE OF EQUIPMENT ACCESS SHOULD BE TAKEN INTO CONSIDERATION.
- B. GROUND SURFACE BENEATH THE FILTER BAG SHALL BE A WELL-VEGETATED, GRASSY AREA WITH LESS THAN A 5% SLOPE. NON-ERODIBLE MATERIAL SHALL BE PLACED UNDER THE FILTER BAG WHERE REQUIRED TO PROVIDE A GROUND SURFACE WITH LESS THAN A 5% SLOPE.
- C. PUMP DISCHARGE HOSE SHALL BE INSERTED INTO THE BAG AND SECURELY CLAMPED AS SPECIFIED BY THE MANUFACTURER.
- D. COMPOST FILTER SOCKS SHALL BE INSTALLED AROUND THE DOWNHILL SIDE OF THE FILTER BAG TO COVER ALL POSSIBLE PATHS OF DISCHARGE FROM THE FILTER BAG.
- E. THE FILTER BAG DISCHARGE PATH SHALL BE ON A NATURAL, NON-ERODIBLE SURFACE, IF AVAILABLE; IF NOT AVAILABLE, A GEOTEXTILE UNDERLAYMENT AND FLOW PATH SHALL BE PROVIDED.
- F. FILTER BAGS SHALL BE INSPECTED DAILY AND REPLACED WHEN THEY BECOME HALF-FULL.
- G. IF A PROBLEM OCCURS WITH THE PUMPING SYSTEM OR FILTER BAG, PUMPING SHALL STOP IMMEDIATELY AND NOT RESUME UNTIL THE PROBLEM HAS BEEN IDENTIFIED AND CORRECTED.
- H. PUMPING SYSTEM AND FILTER BAG SHALL BE REMOVED UPON COMPLETION OF CONSTRUCTION REQUIRING IT'S USE.
- I. ANY LAND DISTURBED BY THE PUMPING SYSTEM OR PLACEMENT OF THE FILTER BAG SHALL BE RESTORED TO PRE-CONSTRUCTION CONDITIONS.

COMPOST FILTER SOCK (CFS)

- A. CFS SHALL BE INSTALLED PARALLEL TO CONTOURS (SEE PLAN DRAWINGS) WITH ENDS TURNED UP AT 45^ ANGLES.
- B. REMOVE STICKS, ROCKS, HEAVY VEGETATION AND OTHER MATERIAL FROM ANY AREA WHERE CFS IS TO BE INSTALLED.
- C. REMOVE ANY MANUFACTURER'S PROTECTIVE COATING FROM CFS AND DISPOSE OF PROPERLY.
- D. ROLL OUT COMPLETE CFS ALONG GROUND, OR ROLL OUT AND FILL CFS IN-PLACE WITH COMPOST.
- E. PLACE STAKES IN THE CENTER OF THE CFS AND SECURE TO THE GROUND. STAKE TYPE, SIZE, SPACING AND DEPTH REQUIREMENTS SPECIFIED BY CFS MANUFACTURER SHALL BE MET.
- F. SEDIMENT CAPTURED BY THE CFS SHALL BE REMOVED WHEN SEDIMENT HEIGHT REACHES 1/2 THE HEIGHT OF THE CFS.
- G. CONSTRUCTION EQUIPMENT SHALL NOT BE DRIVEN OVER ANY INSTALLED CFS.
- H. BIODEGRADABLE CFS SHALL BE REPLACED EVERY 6 MONTHS; PHOTODEGRADABLE CFS SHALL BE REPLACED EVERY 12 MONTHS.
- I. UPON STABILIZATION OF DISTURBED AREA ABOVE INSTALLED CFS, THE STAKES SHALL BE REMOVED, THE CFS CUT OPEN, AND THE MULCH (COMPOST) SPREAD OVER THE SURROUNDING GROUND SURFACE. CFS MESH AND STAKES SHALL BE REMOVED FROM THE AREA AND DISPOSED OF PROPERLY.

NON-ERODIBLE MATERIAL (TEMPORARY ACCESS ROAD/CONTRACTOR LAYDOWN AREAS)

- A. STOCKPILE AASHTO #1 STONE FOR DAILY REPAIR REQUIREMENTS. MAINTAIN 6" (INCH) THICKNESS OF AASHTO #1 THROUGHOUT CONSTRUCTION.
- B. REMOVE ACCUMULATED SEDIMENTS DAILY.
- C. REPLACE ALL ROCK WHEN SURFACE BECOMES CLOGGED WITH SOIL AND THE ABILITY TO TRAP MATERIAL HAS BEEN LOST.

TEMPORARY SLOPE PIPES AND TEMPORARY INLETS

- A. EXCAVATE AND INSTALL R-5 STONE AT TEMPORARY SLOPE PIPE DISCHARGES.
- B. INSTALL TEMPORARY INLETS AND TEMPORARY SLOPE PIPES.
- C. SECURE TEMPORARY SLOPE PIPES LAID ON TOP OF GROUND WITH STAKES OR REBAR DRIVEN INTO THE GROUND TO HOLD PIPES IN PLACES.
- D. INSTALL FILTER BAG INLET PROTECTION WITHIN TEMPORARY INLETS
- E. INSTALL SANDBAG DIVERSIONS ALONG NORTH SPRING STREET
- F. SEDIMENT SHALL BE REMOVED FROM FILTER BAG INLET WHEN ACCUMULATION IS ONE-HALF FULL.

BMP INSTALLATION NOTES (CONTINUED)

PIPE FLUME THROUGH WORK AREA

- A. INSTALL PIPE FLUME WITHIN SULPHUR RUN
- B. INSTALL TEMPORARY SANDBAG DAM UPSTREAM OF DISTURBANCE
- C. INSTALL ROCK FILTER DOWNSTREAM OF DISTURBANCE AREA
- D. TEMPORARY DAM SHALL BE CONSTRUCTED OF SANDBAGS OR OTHER NON-EROSIVE MATERIAL (NO EARTH FILL).
- E. ROCK FILTER SHOULD BE INSPECTED WEEKLY AND AFTER EACH RUNOFF EVENT. NEEDED REPAIRS SHOULD BE INITIATED IMMEDIATELY AFTER THE INSPECTION.
- F. CLOGGED FILTER STONE SHOULD BE REPLACED
- G. SEDIMENT SHALL BE REMOVED WHEN ACCUMULATIONS REACH ONE-HALF THE HEIGHT OF THE FILTER.
- H. IMMEDIATELY UPON STABILIZATION OF SULPHUR RUN, REMOVE ACCUMULATED SEDIMENT. ROCK FILTER AND PIPE FLUME.

BMP MAINTENANCE PROGRAM

BMP INSPECTION SCHEDULE AND RESPONSIBILITIES

- A. EACH BMP SHALL BE INSPECTED AT THE BEGINNING OF EACH WORK DAY BETWEEN 0730 AND 0830, AND AFTER EACH RUNOFF AND HIGH-WATER EVENT.
- B. THE CONSTRUCTION CONTRACTOR QUALITY CONTROL REPRESENTATIVE SHALL CONDUCT THE INSPECTIONS AND NOTE THE FINDINGS IN THE DAILY CONSTRUCTION LOG. ANY DEFICIENCIES OBSERVED OR MAINTENANCE REQUIRED WILL BE NOTED AND THE CONSTRUCTION CONTRACTOR SUPERINTENDENT SHALL BE INFORMED.
- C. THE CONSTRUCTION CONTRACTOR SUPERINTENDENT WILL BE RESPONSIBLE FOR THE REPAIR AND MAINTENANCE OF THE BMP'S.
- D. REPAIR AND MAINTENANCE OF THE BMP SHALL BE PERFORMED THE SAME DAY OR PRIOR TO START OF WORK THE FOLLOWING DAY.

BMP MAINTENANCE INSTRUCTIONS

- A. ROCK CONSTRUCTION ENTRANCE (RCE): AN ADEQUATE SUPPLY OF AASHTO No. 1 STONE SHALL BE STOCKPILED ON-SITE. THE THICKNESS OF THE RCE (8 INCHES) SHALL BE MAINTAINED AT ALL TIMES. ANY SEDIMENT MATERIAL TRACKED OUT ON TO PAVED ROADWAYS SHALL BE REMOVED AND RETURNED TO THE CONSTRUCTION SITE. WASHING THE ROADWAY OR SWEEPING THE DEPOSITS INTO ROADWAY DITCHES, SEWERS, CULVERTS, OR OTHER DRAINAGE COURSES IS NOT ACCEPTABLE.
- B. STONE SHALL BE ADDED TO THE TEMPORARY ACCESS ROAD, TURN-AROUND AREA AND CONTRACTOR LAYDOWN AREA (NON-ERODIBLE AGGREGATE SURFACES) WHEN THE THICKNESS BECOMES LESS THAN 6 INCHES.
- C. FILTERED PUMP OUTFLOW: THE PUMPING RATE SHALL BE NO GREATER THAN 750 GPM OR 1/2 THE MAXIMUM SPECIFIED BY THE MANUFACTURER, WHICHEVER IS LESS. PUMP INTAKES SHALL BE FLOATING SCREENED. FILTER BAGS SHALL BE INSPECTED DAILY. IF ANY PROBLEM IS DETECTED, PUMPING SHALL CEASE IMMEDIATELY AND NOT RESUME UNTIL THE PROBLEM IS CORRECTED. A SUITABLE MEANS OF ACCESSING THE BAG WITH MACHINERY REQUIRED FOR DISPOSAL PURPOSES SHALL BE PROVIDED. FILTER BAGS SHALL BE REPLACED WHEN THEY BECOME 1/2 FULL OF SEDIMENT. SPARE BAGS SHALL BE KEPT AVAILABLE FOR REPLACEMENT OF THOSE THAT HAVE FAILED OR ARE FILLED. BAGS SHALL BE PLACED ON STRAPS TO FACILITATE REMOVAL UNLESS BAGS COME WITH LIFTING STRAPS ALREADY ATTACHED.
- D. COMPOST FILTER SOCK (CFS): SEDIMENT WILL BE REMOVED AND PROPERLY DISPOSED OF WHEN THE ACCUMULATED HEIGHT BEHIND THE CFS REACHES ONE-HALF THE HEIGHT OF THE CFS. UNDERCUT SECTIONS OF THE CFS WILL BE FILLED WITH NSA R-3 STONE. DAMAGED SECTIONS OF THE CFS WILL REMAIN IN PLACE AND A NEW SECTION OF CFS SHALL BE PLACED DIRECTLY UPSLOPE OF THE DAMAGED SECTION OF CFS. THE REPAIR CFS SECTION SHALL EXTEND A MINIMUM OF 4 FEET BEYOND EACH END OF THE DAMAGED SECTION OF CFS. ANY LOOSE OR BROKEN STAKES SHALL BE SECURED OR REPLACED.
- E. AREAS TO RECEIVE VEGETATION SHALL BE MAINTAINED BY RE-SEEDING, MULCHING, FERTILIZING AND WATERING AS NEEDED.

HANDLING AND DISPOSAL OF MATERIALS REMOVED FROM BMP'S

A. SOIL MATERIAL REMOVED FROM THE ROCK CONSTRUCTION ENTRANCE AND FROM BEHIND THE CFS, AS WELL AS ANY PUMPED WATER FILTER BAGS, TREE LIMBS, BRUSH AND OTHER ORGANIC MATERIAL SHALL BE DISPOSED OF OFF-SITE AT A COMMERCIALLY AVAILABLE AND PROPERLY PERMITTED DISPOSAL FACILITY.

CONSTRUCTION WASTES (RECYCLING AND DISPOSAL)

- A. EXCESS SOIL FROM CONSTRUCTION AND DEMOLITION OF THE VARIOUS WORK AREAS SHALL BE DISPOSED OF OFF-SITE AT A COMMERCIALLY AVAILABLE AND PROPERLY PERMITTED DISPOSAL FACILITY.
- B. CONTRACTOR PERSONNEL FOOD, PAPER PRODUCTS AND BOTTLES WILL BE PLACED INTO SEPARATE GARBAGE CANS (PLASTIC AND GLASS BOTTLES FOR RECYCLING) AND SHALL BE DISPOSED OF OFF-SITE AS STATED ABOVE AT THE END OF EACH WORK WEEK.
- C. NON-BIODEGRADABLE CONSTRUCTION WASTES, SUCH AS GEOTEXTILE, PVC PIPE, ETC., SHALL BE DISPOSED OF OFF-SITE AS STATED ABOVE.

BMP MAINTENANCE PROGRAM (CONTINUED)

CLEAN FILL/ENVIRONMENTAL DUE DILIGENCE

- A. THE CONTRACTOR IS RESPONSIBLE FOR ENVIRONMENTAL INVESTIGATIONS FOR ANY OFF-SITE FILL MATERIAL. ALL OFF-SITE FILL MUST MEET PADEP CLEAN FILL STANDARDS.
- B. ALL OFF-SITE BORROW AND/OR WASTE AREAS REQUIRE PRIOR APPROVAL FROM THE INDIANA COUNTY CONSERVATION DISTRICT/PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING THOSE APPROVALS.

TEMPORARY CONTROL MEASURES-VEGETATION

SPECIES:	ANNUAL RYEGRASS
%PURE LIVE SEED:	10%
APPLICATION RATE:	40 LB/ AC
FERTILIZER TYPE:	10-10-10
FERTILIZER APPLICATION RATE:	500 LB/AC
LIMING RATE:	1 TON/ AC
MULCH TYPE:	STRAW
MUI CHING RATE:	2 TONS/ AC

NOTE: SOIL AMENDMENTS AND SEED MIX IN ACCORDANCE WITH THE "EROSION CONTROL AND CONSERVATION PLANTINGS ON NONCROPLAND" MANUAL BY THE COLLEGE OF AGRICULTURAL SCIENCES. PENN STATE UNIVERSITY.

PERMANENT CONTROL MEASURES-VEGETATION

- A. AFTER ALL BMP'S HAVE BEEN REMOVED FROM THE WORK AREA, THE GROUND SURFACE WITHIN THE WORK AREA SHALL BE RETURNED TO PRE-CONSTRUCTION CONDITIONS.
- B. IF THE PRE-CONSTRUCTION AREA WAS VEGETATED, THE AREA SHALL BE RE-VEGETATED AS FOLLOWS:

SPECIES:	PDT 408, SECTION 804.2, FORMULA I
APPLICATION RATE:	2 LB/ 1000 SF
FERTILIZER TYPE:	10-20-20
FERTILIZER APPLICATION RATE:	2 TONS/ACRE
LIMING RATE:	1 TON/ ACRE
MULCH TYPE:	STRAW
MULCHING RATE:	2 TON/ ACRE

AREAS DISTURBED DURING THE CONSTRUCTION ACTIVITY SHALL BE PERMANENTLY SEEDED, FERTILIZED, LIMED AND MULCHED.


CONSTRUCTION SEQUENCE

- A. CONTRACTOR TO ACQUIRE INDIANA COUNTY CONSERVATION DISTRICT WRITTEN APPROVAL OF ALL OFF-SITE WASTE/BORROW AREAS BEFORE AREAS ARE DISTURBED.
- B. LAYOUT THE LIMITS OF EARTH DISTURBANCE OF THE SITE AND ESTABLISH BENCHMARKS AND REFERENCE POINTS.
- C. INSTALL TEMPORARY STREAM CROSSING IN ACCORDANCE WITH CONSTRUCTION DETAILS.
- D. INSTALL CFS IN ACCORDANCE WITH STANDARD CONSTRUCTION DETAIL PRIOR TO CLEARING AND GRUBBING AND OTHER EARTH DISTURBANCE ACTIVITIES.
- E. INSTALL R-5 STONE AT TEMPORARY SLOPE PIPE DISCHARGES, THEN INSTALL TEMPORARY INLETS AND TEMPORARY SLOPE PIPES. SECURE TEMPORARY SLOPE PIPES LAID ON TOP OF GROUND WITH STAKES OR REBAR DRIVEN INTO THE GROUND TO HOLD THE PIPES IN PLACE.
- F. INSTALL FILTER BAG INLET PROTECTION WITHIN TEMPORARY INLETS
- G. INSTALL SANDBAG DIVERSIONS ALONG NORTH SPRING STREET.
- H. INSTALL PIPE FLUME, TEMPORARY UPSTREAM SANDBAG DAM, AND DOWNSTREAM ROCK FILTER.
- I. IF WATER IS ENCOUNTERED DURING STABILIZATION PROCESS A PUMPED WATER FILTER BAG SHALL BE USED FOLLOWING THE TEMPORARY CONTROL MEASURES FOR ITS USE.
- J. INSPECT DOWNSTREAM ROCK FILTER, FILTER BAG INLET PROTECTION, CFS, AND TEMPORARY STREAM CROSSING REMOVE ACCUMULATED SEDIMENT AND DEBRIS TO ALLOW SYSTEMS TO FUNCTION PROPERLY. IF NEEDED, MAKE NECESSARY REPAIRS.
- K. ONCE WORK IS COMPLETE WITHIN THE CULVERT AND THE BANKS ARE ARMORED, REMOVE DOWNSTREAM ROCK FILTER, PIPE FLUME AND TEMPORARY UPSTREAM SANDBAG DAM.
- L. AFTER ROCK FILL HAS BEEN PLACED TO THE LINES AND GRADES SHOWN, REMOVE STAKES AND TEMPORARY SLOPE PIPES AND TEMPORARY INLETS, AND BACKFILL AS REQUIRED.
- M. (IF AWARDED) INSTALL TEMPORARY FLOW DIVERSION STRUCTURE FOR EXTENDED BANK ARMORING; ONCE EXTENDED BANK ARMORING IS COMPLETE, REMOVE TEMPORARY FLOW DIVERSION STRUCTURE.
- N. SEED, FERTILIZER, LIME, AND MULCH AREAS THAT HAVE BEEN DISTURBED BY THE CONSTRUCTION ACTIVITY (AREAS NOT COVERED WITH R-4 RIP RAP).
- O. INSTALL TEMPORARY EROSION CONTROL BLANKETS ON ALL SLOPES GREATER THAN 3H:1V, AND ALONG STREAM BANKS.
- P. REMOVE TEMPORARY STREAM CROSSING AND RESTORE TO EXISTING CONDITIONS AS SHOWN. STONE USED TO CONSTRUCT THE TEMPORARY STREAM CROSSING SHALL BE SPREAD ALONG THE TEMPORARY ACCESS ROAD.
- Q. TREES, BRUSH, EXCESS SOIL AND CONSTRUCTION WASTE FROM THE CONSTRUCTION AND DEMOLITION ACTIVITIES SHALL BE DISPOSED OF OFF-SITE AT AN APPROVED FACILITY.
- R. ONCE THE SITE HAS BEEN STABILIZED AND REACHED A UNIFORM 70% PERENNIAL VEGETATIVE COVER, THE CFS SHALL BE CUT OPEN AND THE WOODEN STAKES AND MESH SHALL BE REMOVED FROM THE SITE AND DISPOSED OF PROPERLY FOLLOWING THE BMP INSTALLATION NOTES.

NOTE:

1. SEE SHEET G-0011 FOR ALL ABBREVIATIONS USED ON THIS SHEET.





U.S. ARMY CORPS OF ENGINEERS

U.S. ARMY CORPS OF ENGINEERS

PITTSBURGH DISTRICT
1000 LIBERTY AVENUE
PITTSBURGH PA, 15222
CHECKED BY:
3. RUSNAK
SUBMITTED BY:
1. RUSNAK
SUBMITT

ANEN I EMBANKMEN I AND CULVER I REPAIR PROJECT
BLAIRSVILLE, PA
ROSION AND SEDIMENT CONTROL PLAN
AANAGEMENT PRACTICE INSTALLATION AND

SHEET ID

X-0006

CERTIFIED FINAL DOCUMENTS