											PA	CK	Ά	SIN	G	RE	QL	JIR	E۱	ИE	NT	S																			
PR, MIPR, OR DOCUMEN	3.														3. INSTRUCTIONS TO CONTRACTING OFFICER: Insert appropriate																										
FD2060-17-93501	22060-17-93501														clause(s) into Section D for applicable item(s) as indicated below.																										
PACKAGING REQUIREMENTS: Block 1 shall always be completed and further defined in Blocks 2, 3, or 4. The term "Item ID" refers to line em number, item name, NSN/MMAC, part number, or any other way of identifying a particular item. MIL-STD-2073-1 represents Military reservation (PRES) and Packing (PACK). Military packing consists of levels A, B, and Minimum (M). ASTM D3951 could be substituted by												AFMC FARS 5352.247-9005, SHIPPING CONTAINER MARKING. NAME(s) OR NSN/MMAC																													
another document if specif	ied in Block	Block 2. Quantity Per Unit (QUP) and Commercial Best Practice (CBP) are abbreviated. The reverse side of n environmental requirements.																		52.24 OR N				RKIN	G O	F WA	\RRA	NTE	D ITE	MS.											
	QUP	MIL-STD-2073-1							MERC M D39			СВ	Р		SPECIAL PACKAGING INSTRUCTION									ł								,			TION						
ITEM ID		F	PRES		PAC	<	PRES PA			PACK	ACK				NUMBER										PACKAGING (ASTM D3951). ITEM NAME(s) OR NSN/MMAC																
	(#)		(X)	(A/B/N	1)	((X)		(X)		(X)											ŀ	_	EMC	E A D	2 52	52 2/	17.0	റവ	CO	NITD	٨٥٦		- M	MED	CIAI			
DELIVERABLES	1	X B												_	AFMCFARS 5352.247-9008, CONTRACTOR COMMERCIAL PACKAGING (Commercial Best Practice). ITEM NAME(s) OR																										
																								-	N	SN/N	ИМА	Э.													
																								- - - [52.24 OR N					₹Y P	ACK	AGIN	IG Al	ND M	ARK	ING.	•
						 -																		- †	_			. ,						FRI	ED O	R SE	PECL	Δ1 17F	:D		
																								_											R NS						
																								_ [_																
2. ADDITIONAL PACKAGII Items shall be packag Shipping and storage	ged in acco	orda	ınce	with	ı MI	L-S	TD.	-20	73-1	E, S	tano	lard	Pra	ctice	fo	r Mi	lita	ıry F	acl	kag	ing.											,			ANI OR				=		
Marking.																																									
																																			G DA' OR N				/or/S	Spec	ial
4. CODED DATA: Coded	requirement	s sh	all be	inter	oretec	d in a	accor	dan	ice wit	h MIL-	STD	-2073	3-1																												
		QUANTITY PRES C PRES WRAP CUSH C UNIT INT C SPEC UNIT PACK WEIG													VEIGH	ΗТ	T UNIT PACK SIZE UNIT PACK CUBE P																								
		QUF	> 	IC	Q	ME	TH	D	MTL	MTI	_ [NNUC	T	CONT	Γ (CONT	L	MŁ	(G		- 1		1	10	LEN	GTH	10	W	IDTH	+	10	DEF	PTH	10	W	HOLE	CUE	E	1000	TH	1
		_																																_	<u> </u>	\sqcup					
																																		╙	igspace	Ш					
																																				Ш					
																															Ī			T							
		L													↥											Ţ				1				I	1				L		
ORGANIZATION									lame)	NIDZ	/40′	7 (2	12	Р	ACI	KAGII	NG S	SPEC	CIAL	IST	SIGI	NAT	URE												DA	ΤE	201	1701	20		
406 SCMS/GULAA	//	//SIGNED//LORENDA MARTINEZ/497-6313											20170130									30	,																		

INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES

REVISION OF ISPM NO. 15

REVISION OF WOOD PACKING MATERIAL FOR INTERNATIONAL TRADE

REQUIREMENTS, USE THE LATEST REVISION OF (ISPM NO. 15)

THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS – IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES, SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES, RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP) OR OTHER BASES).

WOODEN LUMBER, WOODEN PALLET, AND PACKAGING/CONTAINER STATEMENT:

ALL WOODEN LUMBER, WOODEN PALLETS AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM
DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES).
CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE
LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (ISPM NO. 15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."