

Expandable/Collapsible Baton
TECHNICAL REQUIREMENTS/Statement of Work

1. **Background:** The Federal Bureau of Prisons (Bureau) has a requirement for the procurement of expandable/collapsible batons.
2. **Scope:** This statement of work (SOW) delineates the required performance criteria for the acquisition of expandable/collapsible batons.

The technical requirements for the expandable/collapsible batons are specified in section 3:

3. Technical Requirements

3.1 Expandable/Collapsible Baton

- The expandable/collapsible batons shall be black in color and have a corrosion resistant coating on the metallic portions of the baton.
- The batons will be three stage telescoping design with hardened and tempered tubing main construction. Each section will have corrosion resistant coating on the inside and outside of the hardened steel tubing.
- The baton shall be able to be expanded by use of inertia or by the manually grasping the ends of the baton and pulling to expand. When using the manual procedure to open the baton, a minimum of effort shall be required to expand the baton.
- The baton shall be locked open by use of a mechanical c action. The locking mechanism will provide a positive lock with no possibility for collapse without actively actuating the unlocking mechanism. Friction lock actions are not acceptable.
- The Baton shall be collapsed by the use of a release button on the end cap at the butt of the baton. When collapsing the baton, a minimum of effort shall be needed to collapse the baton. No striking of the baton should be required to collapse the baton. The

end cap shall be flared to a minimum of 1 ½" to aid in the retention of the baton during use.

- The baton shall have a length of no less than 9" and no more than 12" when collapsed and no less than 22 and no more than 24 when expanded.
- The baton shall weigh between 18 and 26 ounces.
- The grip section of the baton shall have a diameter of 1" to 1 ¼". The grip section will have either a resilient rubberized or resilient foam covering to aid with retention.
- The striking end of the baton shall have a hardened weighted rubber tip.
- The contractor shall provide a sample of the batons to be evaluated. The samples provided shall be free of manufacturing defects and be the same in every aspect as the batons the company will provide should the contract be awarded.
- Delivery of the batons must take place within 90 days after contractor receives completed forms and accurate purchase document.
- The batons shall have a one-year warranty against defects in materials and workmanship.
- The Contractor shall offer a holster for use with the baton. The holster will be black in color and constructed of durable materials such as Kydex, leather, or reinforced nylon.
- The holster will have a belt clip that will accommodate 1 ½" to 2 ¼" duty belts. The belt clip shall be adjustable to maintain the holster in a vertical position, canted approximately 20 degrees forward, or 20 degrees rearward.
- The baton shall be secured within the holster collapsed with the handle end up. The baton shall be retained in the holster by completely enclosing the baton tip end within the holster
- The holster will be approximately 9" in length.
- Delivery of the holsters must take place within 90 days after contractor receives completed forms and accurate purchase document.

- The holster shall have a one-year warranty against defects in materials and workmanship.

4. Deliverables and Delivery Schedule: Deliverables shall be shipped within 90 days after receipt of order (ARO). Delivery shall be **FOB Destination**. Specific locations, POCs and contact phone numbers will be provided with each delivery order.

The delivery schedule will be provided per each individual delivery order.

4.2 Packing and Marking: Preservation, packaging, packing and marking of the items supplied and delivered under this contract shall be in accordance with current industry standards in order to prevent any deterioration and/or damage during shipping, handling, and storage, and to insure acceptance by common carrier and safe arrival at destinations. All packaging shall state "For the Security Officer Only" on the outside of the shipping packages.

5. WARRANTY: The baton will be warranted for one year to be free of defects in materials and workmanship. The holster shall have a one-year warranty against defects in materials and workmanship.

5.1 Vendor shall provide a warranty letter which delineates all warranty coverage and timeframes.

5.2 Vendor shall be contacted by the Contracting Officer Representative (COR), or an authorized representative of Bureau, for all warranty work.

5.3 Vendor shall provide a primary point of contact, to include phone number and email address.

5.4 Vendor shall acknowledge receipt of warranty claims to the government appointed COR within two business days of being notified.

5.5 Warranty claims shall be remedied at no expense to the government except for shipping to the factory.

6. Government -Furnished Equipment and Information: N/A

7. Place of Performance: CONUS, Alaska, Hawaii, and Puerto Rico. Please refer to <https://www.bop.gov/> for the locations.

8. Period of Performance (PoP): Base Period of 12 months from date of award with one (4) 12-month option periods. Total POP not to exceed 60 months.

9. Special Considerations:

9.1 The Bureau requires Electronic invoicing. Electronic invoices will be sent to the recipients as delineated in each delivery order (DO). Email addresses will be provided for all recipients upon issuance of a DO.

9.2 Shipment specific packing slips shall also contain a list of serial numbers included with that shipment.